

**Model ViO30-6**  
**Year 2015**

**Serial 65345**  
**Hours 601**

**Photos taken at Feb. 26, 2024**





**ヤンマー-グローバルバックホー ViO30-6**

項目	仕様	キャノピ		キャビン	
		標準	別働安全衛生法による 最も不利な仕様	標準	別働安全衛生法による 最も不利な仕様
機械総質量 kg		3215	3680	3385	3810
平均接地圧 kPa(kgf/cm <sup>2</sup> )		30.7(0.313)	35.3(0.360)	32.3(0.330)	36.6(0.373)
輸送時質量 kg		2980	3430	3150	3560
機体質量 kg		2180	2500	2350	2630
定格出力 kW( PS )		18.5(25.2)			
最高走行速度 km/h		前進 4.5		後進 4.5	
・バケット容量	0.08~0.11 m <sup>3</sup>	・つかみ具		・鉄骨切差具 240 kg	
・バケット質量	71~75 kg	・アタッチメント		・コンクリート圧砕具 (クイックヒッチ仕様: 215 kg)	
・最大積載質量 (含バケット)	240 kg	・装着可能質量		・ブレーカユニット	
	(クイックヒッチ仕様: 215 kg)				
アタッチメント装着可能質量は本体の安定度から計算された最大の質量である。					
つかみ具・・・挿込んだ物の質量含む		ブレーカユニット・・・性能上適合する最大質量: 210 kg			

**ヤンマー-建機株式会社**

172902-03102













































