

Model ViO30-6  
Year 2014

Serial 63967  
Hours 2269

Photos taken at May 26, 2023







# ヤンマー-クローラバックホー

# Vio30-6

項目	仕様	キャノピ		キャビン	
		標準	労働安全衛生法による 最も不利な仕様	標準	労働安全衛生法による 最も不利な仕様
機械総質量	kg	3215	3590	3385	3760
平均接地圧	kPa(kgf/cm <sup>2</sup> )	30.7(0.313)	34.4(0.351)	32.3(0.330)	36.1(0.368)
輸送時質量	kg	2980	3340	3150	3510
機体質量	kg	2180	2450	2350	2620
定格出力	kW(PS)	18.5(25.2)			
最高走行速度	km/h	前進 4.5		後進 4.5	
・バケット容量	: 0.08~0.11 m <sup>3</sup>	アタッチメント 装着可能質量 (クイックヒッチ仕様: 215 kg)	つかみ具 鉄骨切断具 コンクリート圧砕具 (ブレイカユニット)	240 kg	
・バケット質量	: 71~75 kg				
・最大積載質量(各バケット)	: 240 kg				

アタッチメント装着可能質量は本体の安定度から計算された最大の質量である。

つかみ具・・・掘んだ物の質量含む      ブレイカユニット・・・性能上適合する最大質量: 210 kg

**ヤンマー-建機株式会社**

172802-03101



























































