

Model ViO30-6

Serial 63967

Year 2014

Hours 2275

Photos taken at Feb. 28, 2024









仕様		キャノピ		キャビン	
項目	標準	労働安全衛生法による 最も不利な仕様	標準	労働安全衛生法による 最も不利な仕様	
機械総質量 kg	3215	3590	3385	3760	
平均接地圧 kPa(kgf/cm ²)	30.7(0.313)	34.4(0.351)	32.3(0.330)	36.1(0.368)	
輸送時質量 kg	2980	3340	3150	3510	
機体質量 kg	2180	2450	2350	2620	
定格出力 kW(PS)	18.5(25.2)				
最高走行速度 km/h	前進 4.5		後進 4.5		
・バケット容量	0.08~0.11	m ³	アタッチメント 装着可能質量 (ブレーカユニット)	240 kg	・鉄骨切断具 ・コンクリート圧砕具 (クイックヒッチ仕様: 215 kg) (ブレーカユニット)
・バケット質量	71~75	kg			
・最大積載質量(含バケット)	240	kg			
	(クイックヒッチ仕様: 215 kg)				
アタッチメント装着可能質量は本体の安定度から計算された最大の質量である。					
つかみ具・・・掘んだ物の質量含む		ブレーカユニット・・・性能上適合する最大質量:		210 kg	

ヤンマー建機株式会社

172002-03101





















































